

Electronic thermostat with external digital LED display for accurate control and easy reading.

Interior cabinet is bright white aluminum liner with full stainless steel floor with coved corners.

Three adjustable, heavy-duty epoxy-coated wire shelves.

Self-contained capillary tube system using environmentally friendly CFC-free refrigerant.

Exterior cabinet construction consists of full stainless steel front and sides.

Condensate heating element built into the condensate pan for efficient evaporation of excess water.

Bottom-mounted compressor for more efficient operation in the coolest area of the kitchen.

Self-closing lockable doors.



Magnetic door gasket is removable and replaceable without tools.

Field reversible, lockable door with foamed-in-place recessed handle.

Larger fan motor and blades for more efficient air flow ensuring faster recovery times.

Unit holds full size sheet pans front to back.

Easy-to-mount casters (two lockable) are standard with all units.

All products are pressurized with environmentally friendly and more efficient Hydrocarbon gas

Front-accessible, bottom-mounted condensing unit is mounted on a slide-out rack for easy maintenance.

Tested to NSF Standard 7 requirements for food storage

Full three-year parts and labour warranty and a five-year compressor warranty.

| Model   | Refrigerant | Number Of Doors | Number Of Shelves | Capacity (CU-FT) | HP | Voltage  | Amps | Nema  | Dimensions (Inches) W x D x H | Shipping Weight |
|---------|-------------|-----------------|-------------------|------------------|----|----------|------|-------|-------------------------------|-----------------|
| CF48GDM | R290        | 2               | 8                 | 48               | 1  | 115/60/1 | 9    | 5-15P | 54.02 x 31.89 x 81.49         | 580lbs          |

