

Added space allows for extra row of pans.

Full length, heavy-duty 5/8" thick cutting board is included.

Exterior cabinet construction consists of full stainless steelfront and sides.

Solid door construction with foamed-in-place recessed handle.

Efficient condensate hot gas loop built into condensate pan for energy saving evaporation of excess condensate water.

All products are pressurized with environmentally friendly and more efficient Hydrocarbon gas.

Vaulted self closing door that remains open at 90 degrees.

Environmentally friendly R290 Hydrocarbon gas.

Magnetic door gasket is removable and replaceable without tools.



Electronic thermostat with external digital LED display for accurate control and easy reading.

Interior cabinet is bright white ABS liner with full stainless steel floor with coved corners

Easy to mount plate casters (two lockable) are standard with all units.

Larger fan motor and blades for more efficient air flow ensuring faster recovery times.

1/6 size clear Lexan pans included.

Tested to NSF Standard 7 requirements for food storage.

Standard with full three-year parts and labour warranties and a five-year compressor warranty.

| Model | Refrigerant | Number Of Doors | Number Of Shelves | Capacity (CU-FT) | HP | Voltage | Amps | Nema | Dimensions (Inches) W x D x H | Shipping Weight |
|---------|-------------|-----------------|-------------------|------------------|-----|----------|------|-------|-------------------------------|-----------------|
| CMT7230 | R290 | 3 | 3 | 18 | 1/2 | 115/60/1 | 7 | 5-15P | 71.73 x 34.53 x 43.19 | 448lbs |

