



iT0450 with Top Air Discharge kit.

KIT INCLUDES

- ▶ Two solid stainless steel side panels
- ▶ One louvered stainless steel top

INSTALLATION

Disconnect electric power to the ice machine (and dispenser if applicable) at the electric switch box before proceeding.

1. Open front door
2. Remove top panel
3. Remove louvered left and right side panels
4. Install new solid left and right side panels
5. Install louvered top panel
6. Secure front door
7. Apply power

SPECIFICATIONS

NOTE: Top Air Discharge for R-290 Equipment.
(Not to be used with R-410A)

Propane Units

Indigo NXT Ice Machine	Height	Width	Kit
iP0420, iP0620	21.5"	22"	K00557
iP0450, iP0500, iP0600	21.5"	30"	K00554
iP0800	26.5"	30"	K00555
iP1000, iP1200	29.5"	30"	K00556

R410A Units

Indigo NXT Ice Machine	Height	Width	Kit
iT0420, iT0620	21.5"	22"	K00438
iT0450, iT0500, iT0600	21.5"	30"	K00379
iT0900	26.5"	30"	K00439
iT1200	29.5"	30"	K00449
iT1500, iT1900	29.5"	48"	K00481B

Minimum Clearance Requirements

Indigo NXT Ice Machine	Top	Back
0450, 0500, 0600, 0800, 1200	8"	5"
0420, 0620	12"	5"
1500, 1900	12"	5"

FEATURES

- ▶ Transfers air discharge from the sides of the machine to the top by having the louvered panel on the top of the machine rather than the sides.
- ▶ Re-directs the hot air from the ice machine toward the ceiling rather than directly into the working kitchen environment.
- ▶ Ideal for locations where space on side of the machine is less than 8" for Indigo NXT Series 0450-1200 or 12" for Indigo NXT Series 0420, 0620, 1500 and 1900.
- ▶ No hardware needed.



2110 South 26th Street | Manitowoc, WI 54220 | United States
+1.920.682.0161 | 920.683.7589 Fax | manitowocice.com

All indicated Pentair trademarks and logos are property of Pentair. Third party registered and unregistered trademarks and logos are the property of their respective owners. ©2025 Pentair. All rights reserved.