

Grab-and-Go Refrigerated Showcase

Item:	48265	48266	48269	48480
Model:	RS-CN-0530-B	RS-CN-0700-B	RS-CN-1050-B	RS-CN-0440-B

Keep foods fresh and in customer-view with this high performance Grab-and-Go refrigerated showcase.

This open refrigerated display is a perfect addition to any establishment, offering easy access, bright LED lighting and adjustable shelves for flexible merchandise. Designed to save space and energy, it features a night curtain and digital temperature controls to keep products fresh and ready to grab.



48480 - 30"



48265 - 36"



48266 - 48"



48269 - 72"

FEATURES:

- Pull down curtain
- LED lighting under each shelf
- Adjustable shelves
- Digital temperature control & display
- 4 Casters
- Ventilated cooling system
- Automatic defrost



TECHNICAL SPECIFICATION				
Features	30" wide 15.5 cu.ft. capacity	36" wide with 18.7 cu.ft.capacity	48" wide with 24.7 cu.ft. capacity	72" wide with 37 cu.ft.capacity
Item	48480	48265	48266	43469
Model	RS-CN-0440-B	RS-CN-0530-B	RS-CN-0700-B	RS-CN-1050-B
Capacity	440 L / 15.5 cu. ft.	530 L / 18.7 cu. ft.	700 L / 24.7 cu.ft.	1050 L / 37 cu.ft.
Shelf Load Capacity	25 kg/ 55.1 lbs	25 kg/ 55 lbs	30 kg/ 66 lbs	50 kg/ 110 lbs
Number of Shelves	5	5	5	5
Number of Casters	4	4	4	4
Power	1700 W	1340 W	2650 W	1960 W
Electrical	110V / 60Hz / 1Ph	120V / 60Hz / 1Ph	220V / 60Hz / 1Ph	220V / 60Hz / 1Ph
Temperature Range	2 to 10°C (35.6 to 50°F)	2 - 10°C / 35.6 - 50°F	2 - 10°C / 35.6 - 50°F	2 - 10°C / 35.6 - 50°F
Lamp Power (W)	-	1.44 Watts x 6 (LED)	1.44 Watts x 6 (LED)	1.44 Watts x 6 (LED)
Refrigerant	R290	R290	R290	R290
Rated Current	11.8 A	11.8 A	12	9.6
Foaming Agent	Cyclopentane	C5H10	XPS	C5H10
Net Dimensions (WDH)	30" x 30.1" x 81.5" 762 x 765 x 2070 mm	36" x 30.13" x 81.5" 915 x 765 x 2070 mm	48" x 30.13" x 81.5" 1220 x 765 x 2070 mm	72" x 30.13" x 81.5" 1829 x 765 x 2070 mm
Gross Dimesions	33.9" x 33.5" x 87.8" 862 x 850 x 2230 mm	40" x 33.6" x 84" 1015 x 853 x 2130 mm	52" x 33.6" x 84" 1320 x 853 x 2130 mm	76" x 33.6" x 84" 1930 x 850 x 2130 mm
Net Weight	125.5 kg/ 276.7 lbs	139 kg/ 306 lbs	190 kg/ 418 lbs	242 kg/ 533.5 lbs
Gross Weight	151 kg/ 332.9 lbs	160 kg/ 352.7 lbs	213 kg/ 469.6 lbs	282 kg/ 621.7 lbs

TECHNICAL DRAWING

